# COMAREX 35BL

#### **DESCRIPTION**

- · Industrial protective glove.
- Natural rubber supported glove.
- Available in 5 sizes: 7, 8, 9, 10 and 11.
- Trade unit: 5 pairs, 50 pairs in a transit case.

### **CHARACTERISTICS**

- 100% cotton jersey liner.
- Blue colour double dipped natural rubber coating.
- Wrinkle finish for added grip.
- 21CFR (USA) and European Directives compliant for food contact.
- · Length: approx. 320 mm.

#### **PERFORMANCES**

- · Comfortable for intensive use.
- Very good flexibility.
- Waterproof coating.
- Excellent thermal insulation either in hot (up to 250°C) or cold (down to -20°C) conditions.
- In compliance with the standards EN 420 (General requirements), EN 388 (Mechanical hazards), EN 407 (Heat and/or fire), EN 374 (Chemical and micro-organisms hazards) and EN 511 (Cold) by the notified laboratory IFTH -Institut Français Textile Habillement - Lyon.
- Manufactured under EC quality assurance system carried out by the BSI.

## **APPLICATIONS**

- For major risks.
- · Ideal for handling sharp objects in a messy and/or humid environment.
- · Good grip for a wide sector of activity: construction, glass industry, public works, food industry.

## **LIMITATIONS**

Do not use in contact with pointed objects.

7 / S

M9999414

- · Do not use with a rotating machine in which glove may get caught.
- Suitable for all types of food except acidic foods.



This glove is certified to comply with the essential requirements of European directive EEC/89/686 of December 21\*, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests and manufactured under a CE quality assurance system carried out by a notified body.











EN 407 Heat and fire



EN 374 Chemical hazards



EN 374 Micro-organisms hazards



EN 511



EN 420

5 Dexterity

FN 388

- 3 Abrasion
- 2 Blade cut
- 3 Tear
- Puncture
- EN 407
- Burning behaviour
- 2 Contact heat

EN 374

- 3 A Methanol
- 6 K Sodium hydroxide 40%
- 6 L Sulphurio

EN 511

- Convective cold
- Contact cold
- Water penetration

References

9 / L

10 / XL

II / XXL

8 / M

M9999415

M9999416

M9999417

M9999418



Sizes

Comarex 35BL







